
LIST PRICES





HOLO-KROME Completely Cold Forged

SOCKET SCREWS

SOCKET HEAD CAP SCREWS . FLAT HEAD SOCKET CAP SCREWS SOCKET SET SCREWS . SOCKET HEAD STRIPPER BOLTS . DOWEL PINS SOCKET PIPE PLUGS . SOCKET SCREW KEYS & KEY SETS THE HOLO-KROME SCREW CORP., HARTFORD 10, CONN.

SULLIVAN TOOL & SUPPLY, Inc.

340 CAPITOL AVENUE HARTFORD 1, CONN.





Completely Completely Gold Forged

The results of the method patented, owned, controlled and exclusively used by Holo-Krome in the manufacture of Holo-Krome FIBRO FORGED Socket Screw Products.

Etched cutaway section of a Holo-Krome Socket Head Cap Screw.

A few of the many exclusive Holo-Krome Features:

- 1 Increased strength
- 2 Continuous uncut laterally deflected core fibres
- 3 Continuous unbroken fibres
- 4 Smooth flat top with slight chamfer
- 5 Concentricity of head with body
- 6 Sockets uniformly accurate to full depth of hole, true hexagonal shape, across flat section. Diameter identical top and bottom, no taper, smooth regular walls, well defined corners
- 7 Continuous fibres ending in socket walls
- 8 Reinforced socket walls
- 9 Continuous uncut fibres
- 10 Square shoulders
- 11 Original continuous fibrous structure

SOCKET SCREWS

CONTINUOUS FIBRES

In Socket Head Screws where strength both in the shoulder and in the socket is essential to the finished product, continuous fibres are of vital importance. Fibres originating in the shank should continue uninterrupted, unbroken and uncut around the socket bottom between it and the shoulder of the screw and terminate in the socket walls. The Holo-Krome patented, completely cold forged method results in a continuous fibrous structure. Holo-Krome FIBRO FORGED Socket Screws retain all the strength of the original steel plus the added strength imparted by the completely cold forged process.



Holo-Krome Completely Cold Forged Socket Screws inherently possess a uniformly accurate socket of true hex shape, smooth regular walls with no taper, well defined corners, walls reinforced by continuous fibres, dimensions identical at top and bottom, and with a useful full depth socket providing equal distribution of all the applied leverage of the key.

CONCENTRICITY

Because of the Completely Cold Forged method, concentricity of head and body is positively assured in H-K FIBRO FORGED Socket Screws.

PHYSICAL PROPERTIES

All standard Holo-Krome Socket Screw Products are manufactured from special analysis alloy steel scientifically heat treated to develop the utmost in the necessary physical properties.


APPEARANCE

The ever increasing use of Holo-Krome Socket Screws by alert design and production engineers of machinery, machine tools and parts proves conclusively the benefits of the saving of weight, space and assembly time as well as adding to the sales appeal of the products.












HOLO-KROME SOCKET HEAD CAP SCREWS N.C. (U.S.S.)

NATIONAL COARSE THREAD
CLASS 3 THREAD FIT STANDARD



LIST PRICES PER 100 SCREWS

	The state of the s	Attack and Annual Contract of the same	an in the sales and the		and the public of the second o					LI	JI FK	ICES P	EK I	O SCR	LTTS	
		_					0	Вос	ly Dia	mete	of S	crews				
Wh	Specify ameter F en Orde	irst ring	No. 4 .112	No. 5 .125	No. 6 .138	No. 8 .164	No. 10 .190	1/ ₄ .250	5/ ₁₆	3/ ₈	7/ ₁₆	1/ ₂	5/8 .625	3/ ₄	7/8 .875	1.000
Thr	eads per	Inch	40	40	32	32	24	20	18	16	14	13	11	10	9	8
							On	e Key ir	rcluded	in each	stando	ırd pacl	age.		1	,
		1/4	4.65	4.70	4.75	4.85			0.05							
		3/8	4.70	4.75	4.80	4.90	5.05	5.25	6.25	7.40	8.90	10.20				
		1/2	4.90	4.95	5.00	5.10	5.30	5.50	6.50	7.40	8.30	10.20				
		5/8	5.10	5.15	5.20	5.35	5.55	5.75	6.75	7.70	9.20	10.60				
		3/4	5.35	5.40	5.45	5.60	5.80	6.00	7.00	8.00	9.50	11.00				
		7/8			5.75	5.85	6.05	6.25	7.25	8.50	10.00	11.75				
		1			6.15	6.35	6.55	6.75	7.75	9.00	10.50	12.25	18.00			
		11/4			0.13	7.10	7.30	7.50	8.50	10.00	11.50	13.50	19.75	24.00		
ō		1½				7.85	8.05	8.25	9.25	11.00	12.50	14.75	21.50	26.00		
Head																
		13/4					8.80	9.00	10.00	12.00	13.50	16.00 17.25	23.25	28.00	47.00	F2 (
9		2		7 + 1 7			9.55	9.75	10.75	13.00	14.50		25.00	30.00	47.00	53.0
ב		21/4						10.50	11.50	14.00	15.50	18.50	27.00	33.00	50.00	56.0
_		21/2						11.25	12.50	15.00	17.00	20.00	29.00	36.00	53.00	60.0
£		23/4						12.00	13.50	16.00	18.50	21.50	31.00	39.00	56.00	65.0
Length Under		3						13.50	14.50	17.50	20.00	23.00	33.00	42.00	60.00	70.0
	-	31/4							16.00	19.00	21.50	24.50	35.00	45.00	64.00	75.0
0		31/2							17.50	20.50	23.00	26.00	37.00	48.00	68.00	80.0
		4								24.00	27.00	29.00	41.00	53.00	74.00	88.0
		41/2								28.00		32.00	45.00	58.00	81.00	96.0
		5								32.00		35.00	49.00	63.00	88.00	105.0
		51/2		CLASS			IT					38.00	53.00	68.00	95.00	114.0
		6		S PECIFY	TANDA		DET					41.00	57.00	73.00	102.00	123.0
		61/2	3			ERING						44.00	62.00	79.00	111.00	133.0
		7	On	e Key	in Eac	h Stan	dard					50.00	70.00	86.00	120.00	143.0
		8			Packa	ge						62.00	85.00	102.00	138.00	167.0
Quantity	per Stan	dard Pkg.				100			5	50	1			25		
dd for e	ea. $\frac{1}{4}''$ lgth	. not listed	1.50	1.60	1.70	1.80	1.90	2.00	2.25	2.50	3.00	4.00	5.00	6.50	8.00	10.00
Extra	Short	Code	564	332	332	18	532	316	732	516	516	38	12	916	916	58
Keys	Arm	List	3.20	3.30	3.30	3.40	4.60	5.70	6.90	11.50	11.50	17.00	28.50	40.00	40.00	55.0
per	Long	Code	564L	332L	332L	18L	532L	316L	732L	516L	516L	38L	12L	916L	916L	58L
100	Arm	List	4.20	4.30	4.30	4.40	5.60	6.70	7.90	13.50	13.50	22.00	38.50	55.00	55.00	75.0

Dimensional Data

A Max. Head Diameter	.183	.205	.226	.270	5/16	3/8	7/16	9/16	5/8	3/4	7/8	1	11/8	15/16
Max. Head Height	.112	.125	.138	.164	.190	1/4	5/16	3/8	7/16	1/2	5/8	3/4	7/8	1
Dimension of Socket	5/64	3/32	3/32	1/8	5/32	3/16	7/32	5/16	5/16	3/8	1/2	9/16	9/16	5/8
Nom. Head Side Height	.1026	.1146	.1265	.1503	.1741	.2291	.2864	.3437	.4010	.4583	.5729	.6875	.8020	.9166
Socket Depth		Depth	of Sock	et shall	be as g			le, but vo	rying co	nditions r			e to speci	fy


Items listed above are standard in H-K Special Analysis Alloy Steel and are carried in stock.

SPECIAL. Prices on application. For Stainless Steel Socket Head Cap Screws see Page 16.

Aluminum, Duralumin, Brass, Bronze, Hardware Bronze, Everdur and other non-ferrous metals.

Screws other than those specifically listed are considered Holo-Krome Cap Screws can be furnished in Monel Metal, Screws can be furnished Plated to customer's specifications.

Prices subject to change without notice.



HOLO-KROME CAP SCREWS

N.F. (S.A.E.)

NATIONAL FINE THREAD CLASS 3 THREAD FIT STANDARD



						O	Boo	ly Dia	ımete	r of S	crews		•		
	Specify ameter First	No.	No. 5	No.	No. 8	No. 10	1/4	5/16	3/8	7/16	1/2	5/8	3/4	7/8	1
Wh	en Ordering	.112	.125	.138	.164	.190	.250	.3125	.375	.4375	.500	.625	.750	.875	1.00
Thr	eads per Inch	48	44	40	36	32	28	24	24	. 20	20	18	16	14	14
						One	e Key ir	cluded	in each	standa	rd pack	age.			
	1/4	4.65	4.70	4.75	4.85										
	3/8	4.70	4.75	4.80	4.90	5.05	5.25	6.25							
	1/2	4.90	4.95	5.00	5.10	5.30	5.50	6.50	7.40	8.90	10.20				
	5/8	5.10	5.15	5.20	5.35	5.55	5.75	6.75	7.70	9.20	10.60				
	3/4	5.35	5.40	5.45	5.60	5.80	6.00	7.00	8.00	9.50	11.00				
	7/8			5.75	5.85	6.05	6.25	7.25	8.50	10.00	11.75				
	1			6.15	6.35	6.55	6.75	7.75	9.00	10.50	12.25	18.00			
_/	11/4				7.10	7.30	7.50	8.50	10.00	11.50	13.50	19.75	24.00		
9	11/2				7.85	8.05	8.25	9.25	11.00	12.50	14.75	21.50	26.00		
Head	13/4					8.80	9.00	10.00	12.00	13.50	16.00	23.25	28.00		
-	2					9.55	9.75	10.75	13.00	14.50	17.25	25.00	30.00	47.00	53.0
de	21/4						10.50	11.50	14.00	15.50	18.50	27.00	33.00	50.00	56.0
Under		-								47.00					
	21/2						11.25	12.50	15.00	17.00	20.00	29.00	36.00	53.00	60.0
±6	23/4			****	1333		12.00	13.50	16.00	18.50	21.50	31.00	39.00	56.00	65.0
Length	3						13.50	14.50	17.50	20.00	23.00	33.00	42.00	60.00	70.0
ĭ	31/4							16.00	19.00	21.50	24.50	35.00	45.00	64.00	75.0
•	31/2							17.50	20.50	23.00	26.00	37.00	48.00	68.00	80.0
0	4								24.00	27.00	29.00	41.00	53.00	74.00	88.0
	41/2								28.00	,	32.00	45.00	58.00	81.00	96.0
	5							,	32.00		35.00	49.00	63.00	88.00	105.0
	51/2				1		1				38.00	53.00	68.00	95.00	114.0
	- /2	-	CLASS	TANDA		"									
	6	SP	PECIFY			RST				,	41.00	57.00	73.00	102.00	123.0
	61/2		WHE	N ORD	ERING						44.00	62.00	79.00	111.00	133.0
	7	On	e Key			dard		,			50.00	70.00	86.00	120.00	143.0
	8			Packag	je						62.00	85.00	102.00	138.00	167.0
-	per Standard Pkg.				100				0				25		
	ea. ¼" lgth, not listed	1.50	1.60	1.70	1.80	1.90	2.00	2.25	2.50	3.00	4.00	5.00	6.50	8.00	10.0
Extra	Short Code	564	332	332	18	532	316	732	516	516	38	12	916	916	58
Keys	Arm List	3.20	3.30	3.30	3.40	4.60	5.70	6.90	11.50	11.50	17.00	28.50	40.00	40.00	55.0
per	Long Code	564L		332L	18L	532L	316L	732L	516L	516L	38L	12L	916L	916L	58L
100	Arm List	4.20	4.30	4.30	4.40	5.60	6.70	7.90	13.50	13.50	22.00	38.50	55.00	55.00	75.0

A Max. Head Diameter	.183	.205	.226	.270	5/16	3/8	7/16	9/16	5/8	3/4	7/8	1	11/8	15/16
H Max. Head Height	.112	.125	.138	.164	.190	1/4	5/16	3/8	7/16	1/2	5/8	3/4	7/8	1
Dimension of Socket	5/64	3/32	3/32	1/8	5/32	3/16	7/32	5/16	5/16	3/8	1/2	9/16	9/16	5/8
S Nom. Head Side Height	.1026	.1146	.1265	.1503	.1741	.2291	.2864	.3437	.4010	.4583	.5729	.6875	.8020	.9166
Socket Depth		Depth	of Sock	et shall	be as g				arying co		render it	inadvisabl	e to speci	fy

Sizes printed in BLACK are STANDARD in H-K Special Analysis Alloy Steel and are carried in stock. Sizes printed in COLOR are SPECIAL and made to order only.

For Stainless Steel Socket Head Cap Screws see Page 16. Holo-Krome Cap Screws can be furnished in Monel Metal, Aluminum, Duralumin, Brass, Bronze, Hardware Bronze, Everdur and other nonferrous metals. Screws can be furnished Plated to customer's specifications. schedule for service charges. Prices subject to change without notice.




HOLO-KROME SET SCREWS

N.C. (U.S.S.)

CUP

NATIONAL COARSE THREAD CLASS 3 THREAD FIT STANDARD




LIST PRICES PER 100 SCREWS

								_							-	
		4						O	Diame	eter o	f Scre	ws				
	Specify ameter l hen Orde	First F	No. 4 .112	No. 5 .125	No. 6 .138	No. 8 .164	No. 10 .190	1/ ₄	5/ ₁₆	3/ ₈	⁷ / ₁₆	1/ ₂	5/8 .625	3/ ₄	7/8	1
Th	reads per	Inch	40	40	32	32	24	20	18	16	14	13	11	10	.875	1.00
							One	Kev in	cluded	in each	standa	rd pack	age.		1	
		1/8	3.95	4.00	4.05	4.10				1						1
		3/16	4.00	4.05	4.10	4.15	4.20	4.30								
		1/4	4.05	4.10	4.15	4.20	4.25	4.35	4.45	4.55						
	-	5/16	4.10	4.15	4.20	4.25	4.30	4.40	4.50	4.60						,
		3/8	4.20	4.25	4.30	4.35	4.40	4.50	4.60	4.70	5.90	6.90				
₹		7/16	4.40	4.45	4.50	4.55	4.60	4.70	4.80	4.90	6.10	7.10				
Over		1/2	4.70	4.75	4.80	4.85	4.90	5.00	5.10	5.20	6.40	7.40	9.90			1
ò		5/8	5.00	5.05	5.10	5.15	5.20	5.35	5.50	5.60	6.80	7.80	10.30	12.80		
		3/4		5.35	5.40	5.45	5.50	5.70	6.00	6.20	7.40	8.40	10.90	13.40		
Length	Service Control of the Control of th	7/8			5.70	5.75	5.80	6.05	6.50	6.80	8.00	9.00	11.50	14.00	17.00	
Le		1			6.00	6.05	6.10	6.40	7.00	7.40	8.70	9.70	12.50	15.00	18.00	23.0
0		11/4		,			6.65	7.10	7.60	8.20	9.50	10.50	13.50	16.00	20.00	25.0
		11/2				EAD F	IT	7.80	8.40	9.20	11.00	12.00	14.50	18.00	22.00	28.0
		13/4			TANDA			8.50	9.20	10.50	12.50	13.50	16.50	20.00	25.00	32.0
		2	SI			ETER FI		9.70	10.50	12.50	14.00	15.00	18.50	23.00	29.00	36.0
		21/2	On			h Stan	dard			14.50	16.50	17.50	21.50	27.00	34.00	42.0
		3			Packag	je			.:			20.00	24.50	31.00	39.00	48.0
Quantity	per Stand	dard Pkg.		1			100				5	0		2	5	
dd for e	ea. $rac{1}{4}''$ lgth	. not listed	1.35	1.40	1.45	1.50	1.55	1.60	1.90	2.25	2.80	3.50	4.75	6.00	7.00	8.00
Extra	Short	Code	050	116	116	564	332	18	532	316	732	14	516	38	12	916
Keys	Arm	List	3.10	3.15	3.15	3.20	3.30	3.40	4.60	5.70	6.90	8.00	11.50	17.00	28.50	40.0
per	Long	Code				564L	332L	18L	532L	316L	732L	14L	516L	38L	12L	9161
100	Arm	List				4.20	4.30	4.40	5.60	6.70	7.90	9.00	13.50	22.00	38.50	55.00

Dimensional Data

C Point Diameter Mean	.053	1/16	.069	5/64	3/32	1/8	11/64	13/64	15/64	9/32	23/64	7/16	33/64	19/32
Dimension of Socket	.050	1/16	1/16	5/64	3/32	1/8	5/32	3/16	7/32	1/4	5/16	3/8	1/2	9/16
Socket Depth		Depth	of Sock	et shall	be as g		practicab finite val				render it i	inadvisab	le to speci	fy

Items listed above are standard in H-K Special Analysis Alloy Steel and are carried in stock. Screws other than those specifically listed are considered SPECIAL. Prices on application. For Stainless Steel Socket Set Screws see Page 17. Holo-Krome Set Screws can be furnished in Monel Metal, Aluminum, Duralumin, Brass, Bronze, Hardware Bronze, Everdur and other non-ferrous metals. Screws can be furnished Plated to customer's specifications. Prices subject to change without notice.



HOLO-KROME SET SCREWS

N.F. (S.A.E.)

NATIONAL FINE THREAD
CLASS 3 THREAD FIT STANDARD

CUP

							0	Diame	eter o	f Scre	ws				
	Specify ameter First en Ordering	No. 4 .112	No. 5	No. 6	No. 8 .164	No. 10 .190	1/ ₄	⁵ / ₁₆	3/ ₈	7/ ₁₆	1/ ₂	5/ ₈	3/ ₄	7/ ₈	1.00
Thr	eads per Inch	48	44	40	36	32	28	24	24	20	20	18	16	14	14
	×					One	Key in	cluded	in each	standa	rd pack	age.			
	1/8	3.95	4.00	4.05	4.10			1	1	1		1 1	l l		
	3/16	4.00	4.05	4.10	4.15	4.20	4.30								
	1/4	4.05	4.10	4.15	4.20	4.25	4.35	4.45	4.55						
	- ·	4.10	4.15	4 20	4 25	4 20	4.40	4.50	4.00						
	5/16	4.10	4.15	4.20	4.25	4.30	4.40 4.50	4.50 4.60	4.60 4.70	5.90	6.90				
=	3/8	4.20	4.45	4.30 4.50	4.35 4.55	4.40		4.80	4.70	6.10	7.10			2 4 5 5 4	
¥	7/16	4.40	4.43	4.30	4.00	4.60	4.70	4.80	4.90	0.10	1.10	1			
Over	1/2	4.70	4.75	4.80	4.85	4.90	5.00	5.10	5.20	6.40	7.40	9.90			
ò	5/8	5.00	5.05	5.10	5.15	5.20	5.35	5.50	5.60	6.80	7.80	10.30	12.80		
	3/4		5.35	5.40	5.45	5.50	5.70	6.00	6.20	7.40	8.40	10.90	13.40		
Length	7/8			5.70	5.75	5.80	6.05	6.50	6.80	8.00	9.00	11.50	14.00	17.00	
9	1			6.00	6.05	6.10	6.40	7.00	7.40	8.70	9.70	12.50	15.00	18.00	23.0
	11/4					6.65	7.10	7.60	8.20	9.50	10.50	13.50	16.00	20.00	25.0
0	11/2		CLASS	3 THE	EAD F	IT	7.80	8.40	9.20	11.00	12.00	14.50	18.00	22.00	28.0
	1 ³ / ₄		_	TANDA			8.50	9.20	10.50	12.50	13.50	16.50	20.00	25.00	32.0
	2	SF			ETER FI		9.70	10.50	12.50	14.00	15.00	18.50	23.00	29.00	36.0
	21/2	On			h Stan		. ,		14.50	16.50	17.50	21.50	27.00	34.00	42.0
	3			Packag	ge						20.00	24.50	31.00	39.00	48.0
Quantity	per Standard Pkg.					100					50		2	5	
dd for e	ea. $\frac{1}{4}$ " lgth. not listed	1.35	1.40	1.45	1.50	1.55	1.60	1.90	2.25	2.80	3.50	4.75	6.00	7.00	8.00
	Short Code	050	116	116	564	332	18	532	316	732	14	516	38	12	916
Extra Keys	Arm List	3.10	3.15	3.15	3.20	3.30	3.40	4.60	5.70	6.90	8.00	11.50	17.00	28.50	40.0
per	Long Code	-			ECAT	332L	18L	532L	316L	732L	14L	516L	38L	12L	916
100	Arm List				564L 4.20	4.30	4.40	5.60	6.70	7.90	9.00	13.50	22.00	38.50	55.0

Dimensional Data

Point Diameter Mean	.053	1/16	.069	5/64	3/32	1/8	11/64	13/64	15/64	9/32	23/64	7/16	33/64	19/32
Dimension of Socket	.050	1/16	1/16	5/64	3/32	1/8	5/32	3/16	7/32	1/4	5/16	3/8	1/2	9/16
Socket Depth		Depth	of Sock	cet shall	be as g		practicab efinite val				render it i	inadvisab	le to speci	fy

Sizes printed in BLACK are STANDARD in H-K Special Analysis Alloy Steel and are carried in stock.

Sizes printed in COLOR are SPECIAL and made to order only.

Consult discount schedule for service charges. For Stainless Steel Socket Set Screws see Page 17. Holo-Krome Set Screws can be furnished in Monel Metal, Aluminum, Duralumin, Brass, Bronze, Hardware Bronze, Everdur and other non-ferrous metals. Screws can be furnished Plated to customer's specifications. Prices subject to change without notice.

7




HOLO-KROME SET SCREWS

N.C. (U.S.S.)

FLAT

NATIONAL COARSE THREAD CLASS 3 THREAD FIT STANDARD



LIST PRICES PER 100 SCREWS


		4						0	Diame	eter o	f Scre	ws			11	
	Specify ameter F ien Orde	irst 💮	No. 4 .112	No. 5 .125	No. 6 .138	No. 8 .164	No. 10 .190	1/ ₄	⁵ / ₁₆	3/ ₈	⁷ / ₁₆	1/ ₂	5/ ₈	3/ ₄	7/ ₈	1.000
The	reads per	Inch	40	40	32	32	24	20	18	16	14	13	11	10	9	8
							One	Key in	cluded	in each	standa	rd pack	age.			
		1/8	3.95	4.00	4.05	4.10				1		·		1	I	
		3/16	4.00	4.05	4.10	4.15	4.20	4.30								
		1/4	4.05	4.10	4.15	4.20	4.25	4.35	4.45	4.55						
	-	5/	4.10	4.15	4.20	4.25	4.30	4.40	4.50	4.60						
		⁵ /16 ³ /8	4.20	4.25	4.30	4.35	4.40	4.50	4.60	4.70	5.90	6.90		*** * * * *		
_			4.40	4.45	4.50	4.55	4.60	4.70	4.80	4.90	6.10	7.10		• • • • •		
■		7/16	4.40	4.43	4.30	4.33	4.00	4.70	4.00	4.30	0.10	7.10			• • • • •	
-		1/2	4.70	4.75	4.80	4.85	4.90	5.00	5.10	5.20	6.40	7.40	9.90			
Over		5/8	5.00	5.05	5.10	5.15	5.20	5.35	5.50	5.60	6.80	7.80	10.30	12.80		
		3/4		5.35	5.40	5.45	5.50	5.70	6.00	6.20	7.40	8.40	10.90	13.40		
Length	-	7/8			5.70	5.75	5.80	6.05	6.50	6.80	8.00	9.00	11.50	14.00	17.00	
e		1			6.00	6.05	6.10	6.40	7.00	7.40	8.70	9.70	12.50	15.00	18.00	23.00
		11/4					6.65	7.10	7.60	8.20	9.50	10.50	13.50	16.00	20.00	25.00
0		11/2		CLASS	3 THE	EAD F	IT	7.80	8.40	9.20	11.00	12.00	14.50	18.00	22.00	28.00
		13/4		S	TANDA	RD		8.50	9.20	10.50	12.50	13.50	16.50	20.00	25.00	32.00
		2	SF			ETER FI		9.70	10.50	12.50	14.00	15.00	18.50	23.00	29.00	36.00
	_	21/2	On			h Stan		, , , ,		14.50	16.50	17.50	21.50	27.00	34.00	42.00
		3			Packag	ge						20.00	24.50	31.00	39.00	48.00
Quantity	per Stand	dard Pkg.					100				5	50		2	5	
Add for e	ea. $\frac{1}{4}''$ lgth.	not listed	1.35	1.40	1.45	1.50	1.55	1.60	1.90	2.25	2.80	3.50	4.75	6.00	7.00	8.00
	Short	Code	050	116	116	564	332	18	532	316	732	14	516	38	12	916
Extra Keys	Arm	List	3.10	3.15	3.15	3.20	3.30	3.40	4.60	5.70	6.90	8.00	11.50	17.00	28.50	40.00
per	Long	Code				564L	332L	18L	532L	316L	732L	14L	516L	38L	12L	916L
100	Arm					4.20	4.30	4.40	5.60	6.70	7.90	9.00	13.50	22.00	38.50	55.00
		List				4.20	4.30	4.40	3.00	0.70	1.50	3.00	13.30	22.00	30.30	33.0

Dimensional Data

G Point Diameter Mean	.053	1/16	.069	5/64	3/32	1/8	11/64	13/64	15/64	9/32	23/64	7/16	33/64	19/32
Dimension of Socket	.050	1/16	1/16	5/64	3/32	1/8	5/32	3/16	7/32	1/4	5/16	3/8	1/2	9/16
Socket Depth		Depth	of Sock	et shall	be as g		practicab efinite val				render it	inadvisab	le to speci	fy

Sizes printed in BLACK are STANDARD in H-K Special Analysis Alloy Steel and are carried in stock.

Sizes printed in COLOR are SPECIAL and made to order only.



HOLO-KROME SET SCREWS



N.C. (U.S.S.)

NATIONAL COARSE THREAD CLASS 3 THREAD FIT STANDARD OVAL

								0	Diame	ter o	f Scre	ws				
	Specify ameter Fir en Orderi		No. 4 .112	No. 5 .125	No. 6 .138	No. 8 .164	No. 10 .190	1/ ₄	⁵ / ₁₆	3/ ₈	7/ ₁₆	1/ ₂	5/ ₈	3/ ₄	7/ ₈	1.000
Thr	reads per In	ch	40	40	32	32	24	20	18	16	14	13	11	10	.875	8
							One	Key in	cluded i	n each	standa	rd pack	age.			
	1.8	1/8	3.95	4.00	4.05	4.10							l	1		1
		16	4.00	4.05	4.10	4.15	4.20	4.30						,		
		1/4	4.05	4.10	4.15	4.20	4.25	4.35	4.45	4.55						
		/4														
		16	4.10	4.15	4.20	4.25	4.30	4.40	4.50	4.60						
		3/8	4.20	4.25	4.30	4.35	4.40	4.50	4.60	4.70	5.90	6.90				
₹	7/	16	4.40	4.45	4.50	4.55	4.60	4.70	4.80	4.90	6.10	7.10				
	1	1/2	4.70	4.75	4.80	4.85	4.90	5.00	5.10	5.20	6.40	7.40	9.90			
Over		5/8	5.00	5.05	5.10	5.15	5.20	5.35	5.50	5.60	6.80	7.80	10.30	12.80		
		3/4		5.35	5.40	5.45	5.50	5.70	6.00	6.20	7.40	8.40	10.90	13.40		
Length		7/			5.70	5.75	5.80	6.05	6.50	6.80	8.00	9.00	11.50	14.00	17.00	
-	1	7/8			6.00	6.05	6.10	6.40	7.00	7.40	8.70	9.70	12.50	15.00	18.00	23.0
ĭ		1/4					6.65	7.10	7.60	8.20	9.50	10.50	13.50	16.00	20.00	25.0
		/4					0.00									
	1	1/2				EAD F	IT	7.80	8.40	9.20	11.00	12.00	14.50	18.00	22.00	28.0
		3/4			TANDA			8.50	9.20	10.50	12.50	13.50	16.50	20.00	25.00	32.0
	2		SP			TER FI		9.70	10.50	12.50	14.00	15.00	18.50	23.00	29.00	36.0
	2	1/2	On			h Stan				14.50	16.50	17.50	21.50	27.00	34.00	42.0
	3			1	Packag	je						20.00	24.50	31.00	39.00	48.0
Quantity	per Standa	rd Pkg.					100				50			2	5	
Add for e	ea. $\frac{1}{4}''$ lgth. r	ot listed	1.35	1.40	1.45	1.50	1.55	1.60	1.90	2.25	2.80	3.50	4.75	6.00	7.00	8.00
F .	Short	Code	050	116	116	564	332	18	532	316	732	14	516	38	12	916
Extra Keys	Arm	List	3.10	3.15	3.15	3.20	3.30	3.40	4.60	5.70	6.90	8.00	11.50	17.00	28.50	40.0
per	Long	Code	-		-	ELAT	2221	101	E22T	21/1	7231	141	E1/T	201	121	01/3
100	Arm				****	564L	332L 4.30	18L 4.40	532L 5.60	316L 6.70	732L 7.90	14L 9.00	516L	38L	12L 38.50	916I
	7	List			****	4.20	4.30	4.40	5.60	6.70	7.90	9.00	13.50	22.00	35.30	55.0

Dimensional Data

Dimension of Socket	.050	1/16	1/16	5/64	3/32	1/8	5/32	3/16	7/32	1/4	5/16	3/8	1/2	9/16
R Point Radius	5/64	3/32	7/64	1/8	9/64	3/16	15/64	9/32	21/64	3/8	15/32	9/16	21/32	3/4
Socket Depth		Depth	of Soci	cet shall	be as g				arying co		render it i	inadvisab	le to speci	fy

Sizes printed in BLACK are STANDARD in H-K Special Analysis Alloy Steel and are carried in stock.

Sizes printed in COLOR are SPECIAL and made to order only.




HOLO-KROME SET SCREWS

N.C. (u.s.s.)

DOG NATIONAL CLASS 3 T

NATIONAL COARSE THREAD CLASS 3 THREAD FIT STANDARD



LIST PRICES PER 100 SCREWS


							0	Diame	ter o	f Scre	ws				
	Specify meter First en Ordering	No. 4	No. 5 .125	No.	No. 8	No. 10	1/4	5/16	3/ ₈	⁷ / ₁₆	1/ ₂	5/8 .625	3/ ₄	7/ ₈	1.000
-	eads per Inch	.112	40	.138 32	.164 32	.190 24	.250 20	.3125 18	16	14	13	11	10	9	8
11111	edds per men	10	10	0.2	02			cluded i		-					
	1/8	3.95	4.00	4.05	4.10										
	3/16	4.00	4.05	4.10	4.15	4.20	4.30								
	1/4	4.05	4.10	4.15	4.20	4.25	4.35	4.45	4.55						
	5/16	4.10	4.15	4,20	4.25	4.30	4.40	4.50	4.60						
	3/8	4.20	4.25	4.30	4.35	4.40	4.50	4.60	4.70	5.90	6.90	1			
₽	7/16	4.40	4.45	4.50	4.55	4.60	4.70	4.80	4.90	6.10	7.10				
	1/2	4.70	4.75	4.80	4.85	4.90	5.00	5.10	5.20	6.40	7.40	9.90			
Over	5/8	5.00	5.05	5.10	5.15	5.20	5.35	5.50	5.60	6.80	7.80	10.30	12.80		
	3/4		5.35	5.40	5.45	5.50	5.70	6.00	6.20	7.40	8.40	10.90	13.40		
Length	7/8	,		5.70	5.75	5.80	6.05	6.50	6.80	8.00	9.00	11.50	14.00	17.00	
<u>a</u>	1			6.00	6.05	6.10	6.40	7.00	7.40	8.70	9.70	12.50	15.00	18.00	23.0
	11/4					6.65	7.10	7.60	8.20	9.50	10.50	13.50	16.00	20.00	25.0
0	11/2			-	EAD F	IT	7.80	8.40	9.20	11.00	12.00	14.50	18.00	22.00	28.0
	13/4			TANDA			8.50	9.20	10.50	12.50	13.50	16.50	20.00	25.00	32.0
	2	SI			ETER FI		9.70	10.50	12.50	14.00	15.00	18.50	23.00	29.00	36.0
	2 ¹ / ₂ 3	On		in Eac Packag	h Stan ge	dard			14.50	16.50	17.50 20.00	21.50 24.50	27.00 31.00	34.00 39.00	42.0 48.0
Quantity	per Standard Pkg.					100		1		5	50	1	2	5	
Add for e	ea. $\frac{1}{4}''$ lgth. not listed	1.35	1.40	1.45	1.50	1.55	1.60	1.90	2.25	2.80	3.50	4.75	6.00	7.00	8.0
Extra	Short Code	050	116	116	564	332	18	532	316	732	14	516	38	12	916
Keys	Arm List	3.10	3.15	3.15	3.20	3.30	3.40	4.60	5.70	6.90	8.00	11.50	17.00	28.50	40.0
per 100	Long Code				564L	332L	18L	532L	316L	732L	14L	516L	38L	12L	916
	Arm List				4.20	4.30	4.40	5.60	6.70	7.90	9.00	13.50	22.00	38.50	55.0

Dimensional Data

Socket Depth		Depth	of Sock	cet shall	be as g		practicab finite val				render it i	inadvisab	le to specif	fy
Half Dog Point Length	.025	.030	.035	.040	.045	1/16	5/64	3/32	7/64	1/8	5/32	3/16	7/32	1/4
P Half Dog Point Diameter Maximum	.070	.083	.092	.109	.127	5/32	13/64	1/4	19/64	11/32	15/32	9/16	21/32	3/4
Dimension of Socket	.050	1/16	1/16	5/64	3/32	1/8	5/32	3/16	7/32	1/4	5/16	3/8	1/2	9/16

Sizes printed in BLACK are STANDARD in H-K Special Analysis Alloy Steel and are carried in stock.

Sizes printed in COLOR are SPECIAL and made to order only.



HOLO-KROME SET SCREWS



N.C. (U.S.S.)

NATIONAL COARSE THREAD CLASS 3 THREAD FIT STANDARD CONE

			•				0	Diame	ter o	f Scre	ws				
	Specify ameter First en Ordering	No. 4	No. 5	No.	No.	No. . 10	1/4	5/16	3/8	7/16	1/2	5/8	3/4	7/8	1
-		112	.125	.138	.164	.190	.250	.3125	.375	.4375	.500	.625	.750	.875	1.00
1111	reads per Inch	40	40	32	32	24	20	18	16	14	13	11	10	9	8
						One	Key in	cluded i	in each	standa	rd pack	age.			
	1/8	3.95	4.00	4.05	4.10			1					I 1	1	l
	3/16	4.00	4.05	4.10	4.15	4.20	4.30								
	1/4	4.05	4.10	4.15	4.20	4.25	4.35	4.45	4.55						
	5/16	4.10	4.15	4.20	4.25	4.30	4.40	4.50	4.60	1					
	3/8	4.20	4.25	4.30	4.35	4.40	4.50	4.60	4.70	5.90	6.90				
=	7/16	4.40	4.45	4.50	4.55	4.60	4.70	4.80	4.90	6.10	7.10				
¥	710	_						1100		0.20				*	
Over	1/2	4.70	4.75	4.80	4.85	4.90	5.00	5.10	5.20	6.40	7.40	9.90			
<u>^</u>	5/8	5.00	5.05	5.10	5.15	5.20	5.35	5.50	5.60	6.80	7.80	10.30	12.80		
	3/4		5.35	5.40	5.45	5.50	5.70	6.00	6.20	7.40	8.40	10.90	13.40		
Length	7/8			5.70	5.75	5.80	6.05	6.50	6.80	8.00	9.00	11.50	14.00	17.00	
ē.	1			6.00	6.05	6.10	6.40	7.00	7.40	8.70	9.70	12.50	15.00	18.00	23.0
_	11/4					6.65	7.10	7.60	8.20	9.50	10.50	13.50	16.00	20.00	25.0
0	11/2		CLASS	3 THE	READ F	IT	7.80	8,40	9.20	11.00	12.00	14.50	18.00	22.00	28.0
	13/4		S	TANDA	ARD		8.50	9.20	10.50	12.50	13.50	16.50	20.00	25.00	32.0
	2	S	PECIFY		ETER FI		9.70	10.50	12.50	14.00	15.00	18.50	23.00	29.00	36.0
	21/2	Or	e Key	in Eac	h Stan	dard			14.50	16.50	17.50	21.50	27.00	34.00	42.0
	3 .			Packa	ge						20.00	24.50	31.00	39.00	48.0
Quantity	per Standard Pk	g.				100					0			25	
Add for e	ea, ½" lgth, not list	ed 1.35	1.40	1.45	1.50	1.55	1.60	1.90	2.25	2.80	3.50	4.75	6.00	7.00	8.00
	Short Cod	e AFA	116		E(4	222	10	F22	216	722		E1/	20	10:	01/
Extra	311011	050	116 3.15	116 3.15	564 3.20	332 3.30	18 3.40	532 4.60	316 5.70	732 6.90	14 8.00	516 11.50	38 · 17.00	12 28.50	916 40.0
Keys	Arm List	3.10	2.13	2.13	3.20	3.30	3.40	4.00	5.70	0.30	8.00	TT:20	17.00	28.30	40.0
per 100	Long Cod	э			564L	332L	18L	532L	316L	732L	14L	516L	38L	12L	9161
	Arm List	1			4.20	4.30	4.40	5.60	6.70	7.90	9.00	13.50	22.00	38,50	55.0


Dimensional Data

Dimension of Socket	.050	1/16	1/16	5/64	3/32	1/8	5/32	3/16	7/32	1/4	5/16	3/8	1/2	9/16
Socket Depth		Depth of Socket shall be as great as practicable, but varying conditions render it inadvisable to specify definite values for this dimension												
Cone Point Angle	\													

Sizes printed in BLACK are STANDARD in H-K Special Alloy Analysis Steel and are carried in stock.

Sizes printed in COLOR are SPECIAL and made to order only.






SET SCREWS N.F. (S.A.E.)

CONE-OVAL HALF DOG & FLAT POINTS

NATIONAL FINE THREAD CLASS 3 THREAD FIT STANDARD




								0)iame	ter of	Scre	ws				
	Specify ameter Fi en Order		No. 4 .112	No. 5	No. 6 .138	No. 8 .164	No. 10 .190	1/ ₄	5/ ₁₆	3/ ₈	7/ ₁₆	1/ ₂	5/ ₈	3/ ₄	7/ ₈	1.006
Thr	eads per li	nch	48	44	40	36	32	28	24	24	20	20	18	16	14	14
	odds por n						One	Key in	cluded i	n each	standa	rd pack	age.			
		1/8	3.95	4.00	4.05	4.10				1			1 1	I		1
		16	4.00	4.05	4.10	4.15	4.20	4.30								
		1/4	4.05	4.10	4.15	4.20	4.25	4.35	4.45	4.55						
	5	/16	4.10	4.15	4.20	4.25	4.30	4.40	4.50	4.60						
_		3/8	4.20	4.25	4.30	4.35	4.40	4.50	4.60	4.70	5.90	6.90				
A	7	/16	4.40	4.45	4.50	4.55	4.60	4.70	4.80	4.90	6.10	7.10				
Over		1/2	4.70	4.75	4.80	4.85	4.90	5.00	5.10	5.20	6.40	7.40	9.90			
ó		5/8	5.00	5.05	5.10	5.15	5.20	5.35	5.50	5.60	6.80	7.80	10.30	12.80		
ŧ		3/4		5.35	5.40	5.45	5.50	5.70	6.00	6.20	7.40	8.40	10.90	13.40		
Length		7/8			5.70	5.75	5.80	6.05	6.50	6.80	8.00	9.00	11.50	14.00	17.00	
	1				6.00	6.05	6.10	6.40	7.00	7.40	8.70	9.70	12.50	15.00	18.00	23.0
0	1	11/4					6.65	7.10	7.60	8.20	9.50	10.50	13.50	16.00	20.00	25.0
		$1\frac{1}{2}$				EAD F	IT	7.80	8.40	9.20	11.00	12.00	14.50	18.00	22.00	28.0
		3/4		_	TANDA			8.50	9.20	10.50	12.50	13.50	16.50	20.00	25.00	32.0
	2	2	SP			TER FI		9.70	10.50	12.50	14.00	15.00	18.50	23.00	29.00	36.0
	2	21/2	On			h Stan	dard			14.50	16.50	17.50	21.50	27.00	34.00	42.0
	3	3			Packag	je						20.00	24.50	31.00	39.00	48.00
Quantity	per Stand	ard Pkg.					100				5	0			25	
Add for e	a. ¼" lgth.	not listed	1.35	1.40	1.45	1.50	1.55	1.60	1.90	2.25	2.80	3.50	4.75	6.00	7.00	8.00
Extra	Short	Code	050	116	116	564	332	18	532	316	732	14	516	38	12	916
Keys	Arm	List	3.10	3.15	3.15	3.20	3.30	3.40	4.60	5.70	6.90	8.00	11.50	17.00	28.50	40.00
per 100	Long	Code				564L	332L	18L	532L	316L	732L	14L	516L	38L	12L	916I
100	Arm	List				4.20	4.30	4.40	5.60	6.70	7.90	9.00	13,50	22.00	38.50	55.0

Dimensional Data

0	Point Diameter Mean	.053	1/16	.069	5/64	3/32	1/8	11/64	13/64	15/64	9/32	23/64	7/16	33/64	19/32
0	Dimension of Socket	.050	1/16	1/16	5/64	3/32	1/8	5/32	3/16	7/32	1/4	5/16	3/8	1/2	9/16
D	Half Dog Point Diameter Maximum	.070	.083	.092	.109	.127	5/32	13/64	1/4	19/64	11/32	15/32	9/16	21/32	3/4
9	Half Dog Point Length	.025	.030	.035	.040	.045	1/16	5/64	3/32	7/64	1/8	5/32	3/16	7/32	1/4
B	Point Radius	5/64	3/32	7/64	1/8	9/64	3/16	15/64	9/32	21/64	3/8	15/32	9/16	21/32	3/4
D	Socket Depth		Depth	of Soci	cet shall	be as g		practicab finite val				render it	inadvisab	le to speci	fy
0	Cone Point Angle	\	Where I	ength i	s the sa	me or she	orter tha	n diamet	er of scre	ew-118	3° ± 2° p 2° is star	oint is sta	ndard.	Where len	gth

Sizes printed in BLACK are STANDARD in H-K Special Analysis Alloy Steel and are carried in stock.

Sizes printed in COLOR are SPECIAL and made to order only.



HOLO-KROME STRIPPER BOLTS N.C. (U.S.S.)

NATIONAL COARSE THREAD CLASS 3 THREAD FIT STANDARD

	C16.	1		0	Shoulder Di	ameter of Be	olts	
Dia	Specify meter Fir en Order		1/ ₄ .246248	5/ ₁₆ .30853105	3/ ₈ .371373	1/ ₂ .496498	5/8 .621623	3/ ₄ .746748
				One K	ey included in ea	ich standard paci	kage.	
	1		16.00	17.00	19.00	29.00		
	1	1/4	16.75	17.75	19.75	29.75	42.75	
	1	1/2	17.50	18.50	20.50	30.50	43.50	68.50
	1	3/4		19.25	21.25	31.25	44.25	69.25
	2			20.00	22.00	32.00	45.00	70.00
	2	1/4			23.50	33.50	48.00	73.00
_	2	1/2			25.00	35.00	51.00	76.00
Length	2	3/4			26.50	36.50	54.00	79.00
	3				28.00	38.00	57.00	82.00
e e	3	1/4			30.50	40.50	61.00	87.00
Shoulder	3	1/2			33.00	43.00	65.00	92.00
S	3	3/4			35.50	45.50	69.00	97.00
0	4				38.00	48.00	73.00	102.00
	4	1/4				52.00	78.00	108.00
	4	1/2				56.00	83.00	114.00
	4	3/4	CLASS 3	THREAD FIT		60.00	88.00	120.00
	5			NDARD AMETER FIRST		64.00	93.00	126.00
	5	1/2	WHEN	ORDERING			108.00	144.00
	6			Each Standard ckage			123.00	162.00
Quantity	per Stand	ard Pkg.	25	25	25	25	25	25
		Code	18	532	316	14	516	38
Extra Keys	Short	List	3.40	4.60	5.70	8.00	11.50	17.00
per	Long	Code	18L	532L	316L	14L	516L	38L
100	Arm	List	4.40	5.60	6.70	9.00	13.50	22.00

Dimensional Data

A Max, Head Diameter	3/8	7/16	9/16	3/4	7/8	1
Nom. Thread Diameter	No. 10-24	1/4-20	5/16-18	3/8-16	1/2-13	5/8-11
Max. Head Height	3/16	7/32	1/4	5/16	3/8	1/2
Dimension of Socket	1/8	5/32	3/16	1/4	5/16	3/8
Nominal Thread Length	3/8	7/16	1/2	5/8	3/4	7/8
Neck Width	5/64	5/64	5/64	3/32	1/8	5/32


All items printed above are standard in H-K Special Analysis Alloy Steel and are carried in stock. Diameters, lengths, threads, metals other than listed are considered SPECIAL. Prices on application. Prices subject to change without notice.



HOLO-KROME FLAT HEAD

N.C. (U.S.S.)

NATIONAL COARSE THREAD CLASS 3 THREAD FIT STANDARD




LIST PRICES PER 100 SCREWS

									2131 1			JO SCR		
		_					O D	iamete	r of S	crews				
	Specify ameter F en Orde		No. 4 .112	No. 5 .125	No. 6 .138	No. 8 .164	No. 10 .190	1/4	5/ ₁₆	3/ ₈	⁷ / ₁₆	1/ ₂	5/ ₈	3/ ₄
Thr	reads per	Inch	40	40	32	32	24	20	18	16	14	13	11	10
						One k	Cey inclu	ded in e	ach stand	dard pac	kage.			
		1/4	5.15	5.25	5.35	,.								
		3/8	5.35	5.45	5.55	5.65	5.75	6.00	6.75					
		1/2	5.55	5.65	5.75	5.85	5.95	6.25	7.00	7.50				
		5/8	5.75	5.85	5.95	6.05	6.15	6.50	7.25	8.00				
A		3/4	5.95	6.05	6.15	6.25	6.35	6.75	7.50	8.50	10.50	12.00		
Ver		1				6.55	7.10	7.50	8.50	9.75	12.00	13.25		
Length Over		11/4					7.85	8.25	9.25	10.75	13.00	14.50	21.00	26.0
engt		11/2					8.50	9.00	10.00	12.00	14.25	15.75	23.00	28.5
		13/4						9.75	10.75	13.00	15.25	17.00	25.00	31.0
0		2						10.50	11.50	14.00	16.25	18.25	27.00	33.5
		21/4							12.25	15.00	17.50	19.75	29.00	36.0
		21/2	CI		THREAD I	FIT			13.00	16.00	18.75	21.25	31.00	39.0
		23/4	,	WHEN C	METER F	3				17.00	20.00	23.00	33.00	42.0
		3	One		ach Star kage	idard		, , , ,		18.00	21.50	25.00	35.00	45.0
Quantity	per Stand	ard Pkg.		1		100				50		2	5	
dd for e	a. ¼″ lgth.	not listed	1.50	1.60	1.70	1.80	1.90	2.00	2.50	3.00	4.00	5.00	6.00	7.00
	Short	Code	116	564	564	332	18	532	316	732	14	516	38	38
Extra Keys	Arm	List	3.15	3.20	3.20	3.30	3.40	4.60	5.70	6.90	8.00	11.50	17.00	17.0
per 100	Long	Code		564L	564L	332L	18L	532L	316L	732L	14L	516L	38L	38L
	Arm	List		4.20	4.20	4.30	4.40	5.60	6.70	7.90	9.00	13.50	22.00	22.0

Dimensional Data

A Max. Head Diameter	.223	.239	.270	.317	.375	.500	.625	.750	.812	.875	1.125	1.375
Dimension of Socket	1/16	5/64	5/64	3/32	1/8	5/32	3/16	7/32	1/4	5/16	3/8	3/8
Socket Depth	D	epth of Sc	ocket shall	be as gre		cticable, b			render it	inadvisab	le to speci	fy

Items listed above are standard in H-K Special Analysis Alloy Steel and are carried in stock. Screws other than those specifically listed are considered SPECIAL. Prices on application. Prices subject to change without notice.




HOLO-KROME FLAT HEAD

OCKET CAP SCREWS

N.F. (S.A.E.)

NATIONAL FINE THREAD
CLASS 3 THREAD FIT STANDARD



Dimensional Data

A Max. Head Diameter	.223	.239	.270	.317	.375	.500	.625	.750	.812	.875	1.125	1.375
Dimension of Socket	1/16	5/64	5/64	3/32	1/8	5/32	3/16	7/32	1/4	5/16	3/8	3/8
Socket Depth	D	epth of So	ocket shall	be as gre	eat as pra defini	cticable, b	ut varying for this din	condition	s render it	inadvisab	le to speci	fy

Sizes printed in BLACK are STANDARD in H-K Special Analysis Alloy Steel and are carried in stock.

Sizes printed in COLOR are SPECIAL and made to order only.




STAINLESS STEEL

CAP SCREWS

N.C. (U.S.S.)

NATIONAL COARSE THREAD
CLASS 3 THREAD FIT STANDARD



LIST PRICES PER 100 SCREWS

		2.5		ALL COMMON SE					FRICES	PER I		EWS	
		4				C	Dian	neter of	f Screw	/s			
	Specify ameter Fi ien Orde		No. 4 N.C. .112	No. 5 N.C. .125	No. 6 N.C.	No. 8 N.C. .164	No. 10 N.C. .190	No. 10 N.F. .190	1/ ₄ N.C. .250	5/16 N.C. .3125	3/8 N.C. .375	1/2 N.C. .500	5/8 N.C. .625
Thr	reads per	nch	40	40	32	32	24	32	20	18	16	13	11
		1/4	5.70	6.00	C 25		1	in each st		1			
					6.25								
		3/8	6.10	6.35	6.55	7.00	7.55	7.55	9.20	12.30			
		1/2	6.50	6.70	6.85	7.40	7.95	7.95	9.60	13.00	17.10		
		5/8	6.90	7.10	7.20	7.85	8.35	8.35	10.20	13.75	17.85		
		3/4	7.35	7.60	7.85	8.25	8.80	8.80	10.75	14.40	18.65	28.75	
		7/8				9.20	9.80	9.80	11.70	15.60	20.00	30.50	
ad		1				9.70	10.30	10.30	12.20	16.15	21.25	31.85	62.30
포		11/4					11.80	11.80	13.90	17.95	23.80	34.85	66.3
der		$1\frac{1}{2}$					13.40	13.40	15.50	19.90	26.50	38.05	74.3
Š		13/4							17.20	21.80	29.15	41.15	79.7
ŧ.	1	2							19.00	23.75	32.00	44.35	85.7
Length Under Head	:	21/4								25.90	34.90	47.75	92.2
ō		21/2								28.05	37.65	51.40	97.7
	-	23/4		CLASS 3 1		IT				30.15	40.65	55.75	103.7
		3	SP	STAN ECIFY DIA	DARD METER FI	RST				32.30	43.70	58.20	109.7
	:	31/4		WHEN O	RDERING					. ,		66.60	115.7
		31/2	One	e Key in E Pacl	ach Stan kage	dard			. ,			70.15	122.85
Quantity	per Stand	ard Pkg.				1	00				50	2	25
F .	Short	Code	564	332	332	18	532	532	316	732	516	38	12
Extra Keys	Arm	List	3.20	3.30	3.30	3.40	4.60	4.60	5.70	6.90	11.50	17.00	28.50
per 100	Long	Code	564L	332L	332L	18L	532L	532L	316L	732L	516L	38L	12L
100	Arm	List	4.20	4.30	4.30	4.40	5.60	5.60	6.70	7.90	13.50	22.00	38.50


Dimensional Data

Max. Head Diameter	.183	.205	.226	.270	5/16	5/16	3/8	7/16	9/16	3/4	7/8
Max. Head Height	.112	.125	.138	.164	.190	.190	1/4	5/16	3/8	1/2	5/8
Dimension of Socket	5/64	3/32	3/32	1/8	5/32	5/32	3/16	7/32	5/16	3/8	1/2
Nom, Head Side Height	.1026	.1146	.1265	.1503	.1741	.1741	.2291	.2864	.3437	.4583	.5729

Sizes printed in BLACK are STANDARD in FM-303 and are carried in stock.

Sizes printed in COLOR are SPECIAL and made to order only.

Consult discount schedule for service charges. All other diameters, lengths, threads, points and types of Stainless Steel Cap Screws are SPECIAL. Prices on application. Prices subject to change without notice.



HOLO-KROME

STAINLESS STEEL EM-203 (18-8) NON-HEAT TREATED

SET SCREWS

N.C. (U.S.S.)

CLASS 3 THREAD FIT STANDARD



POINT ONLY

							O	Dian	neter	of Scr	ews				
	Specify imeter Firs en Orderi		No. 4 N.C. .112	No. 5 N.C. .125	No. 6 N.C. .138	No. 8 N.C. .164	No. 10 N.C. .190	No. 10 N.F. .190	1/ ₄ N.C. .250	5/ ₁₆ N.C.	3/ ₈ n.c. .375	7/ ₁₆ N.C. .4375	1/ ₂ N.C. .500	5/ ₈ N.C. .625	3/ ₄ N.C. .750
Thre	eads per Inc	h	40	40	32	32	24	32	20	18	16	14	13	11	10
							e Key ir	icluded i	n each	standar	d packa	ge.			
	1,	/8	5.00	5.20	5.40	5.55									
	3/	16	5.30	5.45	5.60	5.90	6.30	6.30	6.40						
	1	/4	5.45	5.65	5.80	6.05	6.40	6.40	6.50	6.70					
	5/	16	5.65	5.80	6.00	6.25	6.50	6.50	6.60	6.80	7.40				
	3	1/8	5.80	6.00	6.25	6.50	6.60	6.60	6.70	6.90	7.80	9.65	9.80		
r All	7/	16	5.95	6.15	6.40	6.70	6.80	6.80	6.90	7.20	8.20	9.85	10.10		
Over	1	/2	6.10	6.30	6.55	6.90	7.00	7.00	7.10	7.60	8.70	10.25	10.50	13.90	
gth H		3/8	6.25	6.60	6.90	7.40	7.60	7.60	7.80	8.20	9.40	12.15	12.60	15.80	22.60
Length		3/4			7.15	7.95	8.05	8.05	8.20	9.00	10.00	12.50	14.00	20.75	25.60
0	7	7/8			8.00	8.50	8.70	8.70	8.90	9.80	10.90	14.20	16.60	23.90	30.20
	1					9.20	9.50	9.50	9.80	10.60	12.00	16.10	18.60	26.70	34.50
	1,1	1/4	CL	A55 3	THREAD	FIT	11.10	11.10	11.60	12.40	14.40	19.50	23.10	30.50	39.7
	11	1/2	SPE	STAN CIFY DIA	METER	FIRST			13.40	14.40	16.80	23.70	26.20	34.50	45.2
	13	3/4		WHEN C Key in I	ach Sta	-			15.20	16.40	19.00	26.10	29.50	39.20	50.7
	2			Pac	kage				17.00	18.40	21.20	28.55	32.50	43.70	56.20
Quantity	per Standa	rd Pkg.					100						50		25
Extra Keys	Short Arm	Code List	050 3.10	116 3.15	116 3.15	564 3.20	332 3.30	332 3.30	18 3.40	532 4.60	316 5.70	732 6.90	14 8.00	516 11.50	38 17.0
per 100	Long	Code				564L	332L	332L	18L 4.40	532L 5.60	316L 6.70	732L 7.90	14L 9.00	516L 13.50	38I 22.0
	Arm	List				4.20	4.30	4.30	4.40	5.60	6.70	7.30	9.00	T2.30	22.0

Dimensional Data


C Point Diameter Mean	.053	1/16	.069	5/64	3/32	3/32	1/8	11/64	13/64	15/64	9/32	23/64	7/16
Dimension of Socket	.050	1/16	1/16	5/64	3/32	3/32	1/8	5/32	3/16	7/32	1/4	5/16	3/8
Socket Depth		Depth of	Socket sh	all be as	great as	practicab efinite val	le, but vo	rying con is dimensi	ditions re ion	nder it in	advisable	to specif	у

Sizes printed in BLACK are STANDARD in FM-303 and are carried in stock.

Sizes printed in COLOR are SPECIAL and made to order only.

Consult discount schedule for service charges. All other diameters, lengths, threads, points and types of Stainless Steel Set Screws are SPECIAL. Prices on application. Prices subject to change without notice.

AMERICAN NATIONAL
PIPE THREAD



LIST PRICES PER 100 PLUGS

One Key included in each standard package.

	Americar National		1/16	1/8	1/4	3/8	1/2	3/4	1	11/4	11/2	2
Pi	pe Three	ad	5.00	5.50	7.75	11.00	13.50	23.00	36.00	75.00		
Extra	Short	Code	532	316	14	516	38	916	58	34	SPEC	IAL
Keys	Arm	List	4.60	5.70	8.00	11.50	17.00	40.00	55.00	75.00	MADE	
per	Long	Code	532L	316L	14L	516L	38L	916L	58L	34L	ORD	EK
100	Arm	List	5.60	6.70	9.00	13.50	22.00	55.00	75.00	105.00		
≀uantity	per Stand	ard Pkg.		1	00		5	0		25		

Dimensional Data

Nom. Dia. Large End	.3125	.405	.540	.675	.840	1.050	1.315	1.660	1.900	2.375
Length	5/16	3/8	7/16	1/2	9/16	5/8	3/4	13/16	13/16	7/8
Soc. Width Across Flats	5/32	3/16	1/4	5/16	3/8	9/16	5/8	3/4	1	1
Threads per Inch	27	27	18	18	14	14	111/2	111/2	111/2	111/2

Holo-Krome Socket Pipe Plugs are manufactured of Holo-Krome Special Analysis Heat Treated Alloy Steel. Sockets are uniformly accurate, of true Hexagonal shape — without taper — corners are clean and well defined. . . . Threads are smooth, perfect in lead and pitch, uniformly accurate and held to exceptionally

close tolerances, resulting in the Plugs properly engaging in the tapped hole thus preventing leakage under all and every kind of condition. . . . Holo-Krome can and are furnishing Socket Pipe Plugs made in Brass, Commercial Bronze, Everdur, Duralumin, Stainless Steel or other material.

DRY SEAL PLUGS CAN BE FURNISHED


Prices subject to change without notice.

HOLO-KROME SOCKET SCREW KEYS and KEY SETS

Strong proper fitting keys are as essential as uniformly accurate sockets in socket screws. The value and efficiency of one is determined by the other. Holo-Krome Keys are made of Special Analysis Nickel Alloy Steel held to extremely close limits. Perfect hexagonal shape with both ends burred for rapid application. Correctly proportioned for proper purchase and leverage and scientifically designed to avoid corner strain. Holo-Krome heat treatment produces Keys with "Wear-Hard" surfaces and tough cores, spring tempered. Maximum resistance to torsional and right angle strain is provided and brittleness is eliminated. The "HK" Keys will not round off at the corners or mar the Sockets—can be repeatedly used without deformation in any way.

Holo-Krome Key Sets contain the right quantity and the correct sizes for the greatest number of Socket Screw applications within each Set classification. The modern appearing plastic cases are light weight yet strong and durable. The covers have snap fasteners. For convenience, some of the "HK" Key Sets have individual pockets for the Keys.

Sets No. 44 and 66 are furnished in heavy gauge metal boxes with crackle finish enamel. There are regular hinges on the snap-on covers. Metal separators permit Keys to be placed in groups according to sizes. These sets fit tool boxes and can be carried in the coat or work apron pocket.





When ordering Keys for any type of Socket Screw, specify Key Code Number or diameter of particular screw for which key is intended.

Interchangeability Table

	Sc	rew Diamete	ers		Quantity	Key Required	Codes	and List Pr	ices per	100 Keys
Socket SET	Socket Head CAP	FLAT HEAD Socket	Socket Head STRIPPER	Socket PIPE	per Standard	Hex Across	Sho	rt Arm	Lon	g Arm
SCREWS	SCREWS	Cap Screws	BOLTS	PLUGS	Package	Flat	Code	List	Code	List
#2					100	.035	035	3.10		
#3 & #4	#1				100	.050	050	3.10		
#5 & #6	#2	#4		* * *	100	1/16	116	3.15		
#8	#3 & #4	#5 & #6			100	5/64	564	3.20	564L	4.20
#10 & #12	#5 & #6	#8			100	3/32	332	3.30	332L	4.30
1/4	#8	#10	1/4		100	1/8	18	3.40	18L	4.40
5/16	#10 & #12	1/4	5/16	1/16	100	5/32	532	4.60	532L	5.60
3/8	1/4	5/16	3/8	1/8	100	3/16	316	5.70	316L	6.70
7/16	5/16	3/8			50	7/32	732	6.90	732L	7.90
1/2 & 9/16		7/16	1/2	1/4	50	1/4	14	8.00	14L	9.00
5/8	3/8 & 7/16	1/2	5/8	3/8	50	5/16	516	11.50	516L	13.50
3/4	1/2 & 9/16	5/8 & 3/4	3/4	1/2	25	3/8	38	17.00	38L	22.00
7/8	5/8		1		25	1/2	12	28.50	12L	38.50
1 & 11/8	3/4 & 7/8			3/4	25	9/16	916	40.00	916L	55.00
11/4	1			1	25	5/8	58	55.00	58L	75.00
11/2	11/8 & 11/4			11/4	25	3/4	34	75.00	34L	105.00
13/4 & 2	11/2			11/2 & 2	25	1	100	120.00	100L	180.00

Dimensional Data

W Hex	B Length	-	ong Arm	Radius	W Hex	B Length		ong Arm	Radius
Across Flat	Short Arm	Short Series	Long Series	of Bend	Across Flat	Short Arm	Short Series	Long Series	of Bend
.035	1/2	13/8		1/16	1/4	11/8	31/4	51/4	1/4
.050	9/16	13/4		1/16	5/16	11/4	33/4	6	5/16
1/16	9/16	13/4		1/16	3/8	13/8	41/4	63/4	3/8
5/64	39/64	17/8	33/16	5/64	1/2	15/8	51/4	81/4	1/2
3/32	21/32	2	33/8	3/32	9/16	13/4	53/4	9	9/16
1/8	3/4	21/4	33/4	1/8	5/8	17/8	61/4	93/4	5/8
5/32	27/32	21/2	41/8	5/32	3/4	21/8	71/4	111/4	3/4
3/16	15/16	23/4	41/2	3/16	1	25/8	91/4	141/4	1
7/32	11/32	3	47/8	7/32					

HOLO-KROME KEY SETS No. 6 No. 7 No. 103 No. 107 20

SET NO. 6 IN PLASTIC CASE

The ideal set for servicemen on instruments, radios, motors and practically all types of equipment where small diameter screws are used Contains 6 Short Arm Series Keys — $.050 - \frac{1}{16}" - \frac{5}{64}" - \frac{3}{32}" - \frac{1}{8}" - \frac{5}{32}"$ Hex across flat. Fits No. 4 to $\frac{5}{16}"$ Set and No. 4 to No. 10 Socket Cap Screws incl. See Interchangeability Table page 19. Size of case 3" x $\frac{25}{8}"$. Weight in plastic case 2 ozs. 10 Sets in standard package. **List Price \$0.50 each.**

SET NO. 7 IN PLASTIC CASE

Popular sizes for the most used Socket Screw applications. . . . Contains 7 Short Arm Series Keys — 5/64'' - 3/32'' - 1/8'' - 5/32'' - 3/16'' - 7/32'' - 1/4'' Hex across flat. Fits No. 8 to 1/2'' Set and No. 4 to 1/2'' Socket Cap Screws incl. See Interchangeability Table page 19. Size of case 1/2'' x 1/2''. Weight in plastic case 4 ozs. 10 Sets in standard package. **List Price \$0.75 each.**

SET NO. 103 IN PLASTIC CASE

Meets the demands of the Oil Burner Service Men for extra long (6 in.) Keys.... Contains 3 extra long Keys — $\frac{1}{8}$ " — $\frac{5}{32}$ " — $\frac{3}{16}$ " Hex across flat. Fits $\frac{1}{4}$ " to $\frac{3}{8}$ " Set and No. 8 to $\frac{1}{4}$ " Socket Cap Screws incl. See Interchangeability Table page 19. Size of case $\frac{7}{8}$ " x $\frac{21}{16}$ ". Weight in plastic case 3 ozs. 10 Sets in standard package. **List Price \$0.75** each.

SET NO. 107 IN PLASTIC CASE

Popular sizes in the most used Long Arm Series Keys. . . . Contains 7 Long Arm Keys — $\frac{5}{64}"$ — $\frac{3}{32}"$ — $\frac{1}{8}"$ — $\frac{5}{32}"$ — $\frac{3}{16}"$ — $\frac{7}{32}"$ — $\frac{1}{4}"$ Hex across flat. Fits No. 8 to $\frac{1}{2}"$ Set and No. 4 to $\frac{5}{16}"$ Socket Cap Screws incl. See Interchangeability Table page 19. Size of case $\frac{4^3}{4}"$ x $\frac{2^1}{2}"$. Weight in plastic case 6 ozs. 10 Sets in standard package. **List Price \$1.00 each.**

SET NO. 44 IN METAL BOX

Contains 11 Short Arm Series Keys — .050 — $\frac{1}{16}''$ — $\frac{5}{64}''$ — $\frac{3}{32}''$ — $\frac{1}{8}''$ — $\frac{5}{32}''$ — $\frac{3}{16}''$ — $\frac{7}{32}''$ — $\frac{1}{4}''$ — $\frac{5}{16}''$ — $\frac{3}{8}''$. Fits No. 4 to $\frac{3}{4}''$ Set and No. 4 to $\frac{1}{2}''$ Socket Cap Screws incl. See Interchangeability Table page 19. Size of metal box 5" x $\frac{23}{4}''$ x $\frac{3}{4}''$. Weight in metal box 16 ozs. **List Price \$1.50 each.**

SET NO. 66 IN METAL BOX

Contains 13 Short Arm Series Keys — .050 — $\frac{1}{16}$ " — $\frac{5}{64}$ " — $\frac{3}{32}$ " — $\frac{1}{8}$ " — $\frac{5}{32}$ " — $\frac{3}{16}$ " — $\frac{7}{32}$ " — $\frac{1}{4}$ " — $\frac{5}{16}$ " — $\frac{3}{8}$ " — $\frac{1}{2}$ " — $\frac{9}{16}$ ". Fits No. 4 to $\frac{1}{8}$ " Set and No. 4 to $\frac{1}{8}$ " Socket Cap Screws incl. See Interchangeability Table page 19. Size of metal box $\frac{6}{4}$ " x $\frac{4}{2}$ " x $\frac{1}{8}$ ". Weight in metal box 2 lbs. 9 ozs. **List Price \$2.25 each.**

SET NO. 113 IN PLASTIC CASE

Contains 13 Long Arm Series Keys — $.050 - \frac{1}{16}$ " — $\frac{5}{64}$ " — $\frac{3}{32}$ " — $\frac{1}{8}$ " — $\frac{5}{32}$ " — $\frac{3}{16}$ " — $\frac{7}{32}$ " — $\frac{1}{4}$ " — $\frac{5}{16}$ " — $\frac{3}{8}$ " — $\frac{1}{2}$ " — $\frac{9}{16}$ ". Fits No. 4 to 1 ½" Set and No. 4 to ½" Socket Cap Screws incl. See Interchangeability Table page 19. Size of case 11" x 3½". Weight in plastic case 2 lbs. 9 ozs. Packed in individual cardboard box. List Price \$3.00 each.

Prices subject to change without notice.


HOLO-KROME KEY SETS HOLO-KROME HARTFORD CONN. U.S.A. No.44 HOLO-KROME HARTFORD CONN. G.SA No.66 No. 66 No. 113



BLACK LUSTRE FINISH

DOWEL PINS


.0002 OVER LISTED STANDARD



	ipecify 📥				0	Diam	eter of	Dowe	l Pins			
	neter First n Ordering	1/8	3/16	1/4	5/16	3/8	7/16	1/2	5/8	3/4	7/8	1
					ES PER	100 IN E	LACK	PRICES F	PER DOZI	N IN COL	OR	
	3/8	5.00 .60	*****									
	1/2	5.10 .61	5.50 .66	6.10 .73	6.85	7.75 .93						
	5/8	5.20	5.65	6.25 .75	7.05 .85	8.05 .97						
	3/4	5.40 ,65	5.85 .70	6.50 .78	7.35 .88	8.35 1.00		15.10 1.81				
	7/8	5.70 .68	6.15 .74	6.80	7.65 .92	8.65 1.04						
	1	6.00	6.45	7.10 .85	7.95 .95	8.95 1.07	12.90 1.55	16.30 1.96	21.90 2.63			
	11/4	6.60	7.10 .85	7.85 .94	8.90 1.07	10.00 1.20	14.05 1.69	17.50 2.10	23.80 2.86			
¥	11/2	7.30 .88	7.90 .95	8.75 1.05	9.90 1.19	11.25 1.35	15.40 1.85	18.70 2.24	25.70 3.08			
Over	13/4	8.00 .96	8.70 1.04	9.70 1.16	11.00 1.32	12.50 1.50	16.75 2.01	20.00 2.40	27.75 3.33			
Length (2	8.70 1.04	9.50 1.14	10.75 1.29	12.25 1.47	13.75 1.65	18.00 2.16	21.50 2.58	30.00 3.60	42.00 5.04	62.00 7.44	82.00 9.84
Len	21/4			12.00 1.44	13.50 1.62	15.25 1.83		23.30 2.80	32.50 3.90			
0	21/2			13.50 1.62	15.00 1.80	16.75 2.01	21.50 2.58	25.50 3.06	35.00 4.29	49.00 5.88	70.00 8.40	90.0
	3				18.00 2.16	19.75 2.37	25.00 3.00	30.50 3.66	42.00 5.04	60.00 7.20	78.00 9.36	100.0 12.0
	31/2							36.20 4.34	49.00 5.88	72.00 8.64	90.00 10.80	116.00 13.92
	4							42.00 5.04	56.00 6.72	84.00 10.08	104.00 12.48	134.0 16.0
	41/2								64.00 7.68	96.00 11.52	118.00 14.16	152.0 18.2
	5							****	74.00 8.88	108.00 12.96	132.00 15.84	170.0 20.4
	6									132.00 15.84	160.00 19.20	206.0
uantity p	er Standard Pkg.			00		5			25			2

Dimensional Data

_		Maximum	.1253	.1878	.2503	.3128	.3753	.4378	.5003	.6253	.7503	.8753	1.0003
O	Diameter	Minimum	.1251	.1876	.2501	.3126	.3751	.4376	.5001	.6251	.7501	.8751	1.0001
D	Point Diam	eter	.119	.176	.239	.301	.364	.4205	.483	.608	.728	.853	.978
B	Top Radius	s	3/64	3/64	1/16	1/16	5/64	3/32	7/64	1/8	1/8	1/8	1/8



RUST RESISTANT BLACK LUSTRE FINISH

DOWEL PINS

.001 OVER LISTED DIAMETER

OVERSIZE



S	pecify 🔺			0	Diame	ter of Do	owel Pins	5		
	eter First Ordering	1/8	3/16	1/4	5/16	3/8	7/16	1/2	5/8	3/4
1				PRICES PER	100 IN BI	ACK PRI	CES PER D	DZEN IN CO	DLOR	
	3/8	5.00					****			
		.60					*****			
	1/2	5.10	5.50	6.10	6.85					
	72	.61	.66	.73	.82					
		F 00	F 0F	C 05						
	5/8	5.20 .62	5.65 .68	6.25 .75						
	3/4	5.40	5.85 .70	6.50 .78	7.35	8.35 1.00				
	=	.03	.70	.70	.00					
	1	6.00	6.45	7.10	7.95	8.95	12.90	16.30		
		.72	.77	.85	.95	1.07	1.55	1.96		
	11/4	6.60	7.10	7.85	8.90	10.00		17.50		
₹	- /4	.79	.85	.94	1.07	1.20		2.10		
	11/2	7.30	7.90	8.75	9.90	11.25	15.40	18.70		
Over	1/2	.88	.95	1.05	1.19	1.35	1.85	2.24		
	40/	0.00	0.70	0.70	11.00	12.50		20.00		
Length	13/4	8.00 .96	8.70 1.04	9.70 1.16	1.32	1.50		2.40		
Le			0.50	40.75	10.05	13.75	18.00	21,50	30.00	42.00
0	2		9.50 1.14	10.75 1.29	12.25 1.47	1.65	2.16	2.58	3.60	5.04
•										
	$2^{1/4}$		****		13.50 1.62	15.25 1.83		23.30 2.80		
	21/2			13.50	15.00 1.80	16.75 2.01	21.50 2.58	25.50 3.06	35.00 4.20	49.00
				1.62	1.00	2.01	2.30	3.00	7.20	
	3				18.00	19.75	25.00	30.50	42.00	60.00
					2.16	2.37	3.00	3.66	5.04	7.20
	31/2							36.20	49.00	72.00
	- /2		****					4.34	5.88	8.64
	4							42.00	56.00	84.00
	4		****					5.04	6.72	10.08

Dimensional Data

	Maximum	.1261	.1886	.2511	.3136	.3761	.4386	.5011	.6261	.7511
Diameter Diameter	Minimum	.1259	.1884	.2509	.3134	.3759	.4384	.5009	.6259	.7509
Point Diam	neter	.119	.176	.239	.301	.364	.4205	.483	.608	.728
R Top Radiu	s	3/64	3/64	1/16	1/16	5/64	3/32	7/64	1/8	1/8



THE HOLO-KROME SCREW CORP., HARTFORD 10, CONN., U. S. A.